

Castelli Marble

Glacier White


A classic white marble, the white color has various cloud-like hints of blue and rose, adding one-of-a-kind shade variations into your space. Perfect for interior designs cultivating a modern look through luxury tiling, Glacier White's reliable beauty is the perfect foundation for your artistic vision. This marble originates from Mexico.

The stone offers the possibility for custom sizes, finishes, and fabrication. Stocked in a polished finish.






2" Hexagon Mosaic 0.9sf / sh




Octagon Mosaic 1 sf / sh



2" x 4" Brick Mosaic 1 sf / sh



Herringbone Mosaic 0.91 sf / sh



Basketweave Mosaic 1.35 sf / sh



12" x 24" x 3/8"



12" x 12" x 3/8"







5" x 5" x 3/8" Hexagon

Custom Tile Finishes: Honed, Brushed, Tumbled, Chiseled

Applications

Interior	Interior	Shower	Shower	Exterior	Pool /	Fireplace	Commer-	Freeze /
Floor	Wall	Wall	Floor		Fountain	Surround	cial	Thaw
Υ	Υ	Υ	4"x4" & mosaics	Z	Z	Υ	Light	Z


*Standard thickness is 3/8". All dimensions are nominal. Sizes may vary. Products are natural and hand made.

Installation & Maintenance

Grout	Thinset	Installation Instructions	Dry Layout	Cleaner	
Un-sanded	White	TCNA Handbook	Yes	PH neutral	

Variations

 $3'' \times 6'' \times 3/8'$



Indicated is the range of the stone. The higher the number the more variation the tile may exhibit.

Installation & Maintenance Guidelines

- Work with a professional natural stone installer. Consult setting material manufacturers such as Bostick, Mapei & Laticrete on suitability of products.
- Industry standard suggest ordering at least 15% overage due to breakage, tile cuts, and future repairs.
- Veins, natural voids, fissures, variations in color, shade, texture & size are normal in natural stone.
- It is recommended to dry lay all tiles prior to install to achieve the color and pattern desired.
- Sealing natural stone is recommeded before and after grouting, for an easier clean up.
- Sealing your tile regularly helps prevent staining.
- Industry standard deems installation as acceptance of material.